


FIG. 1



	,							,	
FIGURE 2									
FIGURE 1				Model					
KEYWORD				Directional steps					
PUNDAMENTAL KEYWORD FIGURE I				Because a molding method is one carried out by stacking layers			,		
KNOWLEDGE AND WISDOM RELATED TO KNOW-HOW TO BE USED				Resolution in the Z direction exerts an effect	:	·			
REASONS WHY INDESIRABLE RESULTS OCCUR (CAUSE OF UNDESIRABLE INDESIRABLE RESULTS)				Because steps corresponding to stacked layers are the Z direction formed like exerts an effect contours			·		
UNDESIRABLE LESULTS IN CASE WHERE RENOW-HOW IS NOT USED	·			Becomes a surface on which steps are noticeable					
KNOW-HOW				urn a surface hose pearance given nportance to					
CHAPTER CLAUSE (TITLE OF CONTENTS DEMAND OF KNOW-HOW				Appearance in solid on the surfaces whose appearances are given importance in solid one is a flat surface in solid one is a flat surface in the surface in t					
DEMAND				Аррсагансе					
CONTENTS OF WORK				Chap 2 2_01 a reverse surface of surface of surface object					
TITLE OF CLAUSE				Determine a reverse surface					
TAUSE	10_0	1_01	1_02	2_01	2_02	2_03	2_04	3_01	•••
CHAMTER (Chap 0 0_01	Chap 1	Chap 1	Chap 2	Chap 2 2_02	Chap 2 2_03	Chap 2 2_04	Chap 3 3_01	•••




FIG. 4




FIG.5




FIG.6





FIG.7

	_
FILE(F) EDIT(E) DISPLAY(V) FAVORITE(A) TOOL(T) HELP(H)	
ADDRESS f http://xxxxx/xxx.xxx	
USER ID	
PASSWORD	
OK	

FILE(F) EDIT(E) DISPLAY(V) FAVORITE(A) TOOL(T) HELP(H)	
← RETURN	
ADDRESS (€] http://xxxxx/xxx.xxx	
LUSER NAME I USER I I I I I I I I I I I I I I I I I I I	

FIG.9



FILE(F) EDIT(E) DISPLAY(V) FAVOF	RITE(A)	AY(V) FAVORITE(A) TOOL(T) HELP(H)			
◆RETURN _					
ADDRESS la http://xxxxx/xxx.xxx				F	
USER NAME T USER I	СНА	CHAPTER 1 CONVERSION OF SHAPE FOR PLOTTER	E FOR PLOTTER	DETAILS DISPLAY 6	.65
	i —	Ol PLOTTER DATA EDITOR CONVERSION OF SHAPE FOR PLOTTER Select "① editing of a shape for a plotter" from an application menu in protter data	/ERSION OF SHAPE I plotter" from an appl	OR PLOTTER ication menu in protter data	
NETRIEVAL		KNOW-HOW It is also possible to start plotter data editor from a start menu.	to start plotter data e	litor from a start menu.	
CHAPTER 1 KONVERSONOF SWARE CHAPTER 1 KONVERSONOF SWARE		IMAGE		,	
	1_02	STL DATA READING Specify and call an STL file to be converted from a file/registration menu in a window for converting a shape for a plotter. KNOW-HOW It is possible to convert a plurality of data at a time.	converted from a file r. nvert a plurality of da	/registration menu in a winc Ita at a time.	wop
CHAPTER 6 MANUAL MARING SUPPORT CHAPTER 7 DATA TRANSFER CHAPTER 8 REMORT OPERATION CHAPTER 9 SETTING OF LIQUID SURFACE CHAPTER 10 MOLDING ARRANGEMENT		IMAGE	NI VI	IMAGE	
	1 03	PROCESSING CONDITION SETTING Invert the name of a model to be edited, and push "editing/processing conditions setting" to confirm a unit. KNOW-HOW Generally, millimeter is a unit. Confirm because there is a case where inch or the like is a unit.	TTING sdited, and push "editi eter is a unit. Confirm like is a unit.	ng/processing conditions because there is a case	
CHAPTER 16 SECONDARY CURING		IMAGE		IMAGE	

TT(E) DISPL AME T US SKILL! SKILL! SKILL! SLICING CROSS SEC AUTOMATIC I MANUAL MA MANUAL M	AY(V) FAVORITE(A) TOOL(T) HELP(H) XXXXXXXXXXX XXXXXXXXXXXXX SER 3 -
CHAPTER 12 EAROSUKE, TAKAMETEK CHAPTER 13 MOLDING CHAPTER 14 REMOVAL CHAPTER 15 WASHING AND SUPPORT CHAPTER 16 SECONDARY CURING	

FIG.12




FIG.13

				-																																												_	-																			_		_										_	_	_	<u> </u>	_	=	=	[=	_]		三 >	三 く	=
FILE(F) EDIT(E) DISPLAY(V) FAVC	OR	DR)R)F	F	l)]))))))))))	F	F	R	F	F	F	R	R	R	3	3	?	•	IJ	J	ľ	7	Ι	I	Ε	(/	١	٠,)		-	ľ	ľ))(C)	Į	_	(7	Γ)		ŀ	1	I	Ε	L	P	(Н	I))	_			_												_		_	_							_	_	_
□ RETURN □																																		_	_					_		_																	_																								_				_		_					_	_	_
ADDRESS http://xxxxx/xx	xxxx				_	_		_	_	=	=	=	=	=	_	_	_		_	=		_	_	_						_	_	_	_	_	=	_				=			_			_	_					=	=		_	_	_	_	_	_	_	_		_	_	_	_	_		_	_	_	_				_			= =	= =		7	<u>_</u>											_	
	LIST	T (((((•	•										•	((((((((())	F	77.	•]	F	?		ŀ	-			5	1	[j	J	J		,		I			5	•																					_										-				_	
NUMBER OF CLAUSE WORK Proce 1_03 Cond Settir	NAME essing lition					-	-		- 2						- 3 -	- 3 -	- 2 -			1 1 1	1 1 1	1	1	1					T 1 1 1 1 1 1	•	_	-	-		-		r	_	_		_		_	_				_	_		_	_				_	_				_	_	_		_	_	_		_	_	_	_	_		_	_	_	_	W in	_	- <u>-</u> :-	- 1	_		- -	1147111				•						
																																													-						•												•														•								•											
																																								_																					_	1]	ſ	_	_	_			_						=	-		_	_	_				_			_	L	7	=	

FILE(F) EDIT(E) DISPLAY	FILE(F) EDIT(E) DISPLAY(V) FAVORITE(A) TOOL(T) HELP(H)	
← RETURN		
ADDRESS http://xxxxx/xxx.xxx	x/xxx.xxx	Δ
	DETAILS DISPLAY	AY DETAILS DISPLAY 66
KNOW-HOW	Generally, millimeter is a unit. Confirm because there is a case where inch or the like is a unit.	or the like is a unit.
RELATED IMAGE	IMAGE	IMAGE
CASE WHERE THIS KNOW-HOW IS NOT USED	Molded in different size	

FIG.15

FILE(F) EDIT(E) DISPLAY(V) FAVORITE(A)	TOOL(T) HELP(H)	
→ RETURN		
ADDRESS Attp://xxxxx/xxx.xxx	V	
LIST OF	RESULTS	_
FAILURE A molding time period is lengthened.	CAUSE Because it takes long to perform exposure and coating per layer.	- 1 -1 -1
A knife is brought into contact with a model for a long time so that the model is liable to be destroyed when a molding time period is increased and the knife moves.	Because the distance a knife moves is increased, and the probability that the knife is caught by the model is increased.	-

FIG.16

		_ D ×
FILE(F) EDIT(E) D	ISPLAY(V) FAVORITE(A) TOOL(T) HELP(H)	·
♦RETURN		
ADDRESS http:	//xxxxx/xxx.xxx	
	DETAILS DISPLAY	DETAILS DISPLAY 66
FAILURE CAUSE KNOW-HOW AT THIS TIME RELATED IMAGE RELATED KNOWLEDGE	A molding time period is lengthened. Because it takes long to perform exposure ar When it is desired to shorten a molding time period, the is reduced to make the number of stacked layers as small. Rotate by editing of a shape for a plotter in the dir the height is minimized.	height in the Z direction l as possible.

FIG.17

